

Agitatore Digital Orbital Shaker

Digital Orbital Shaker, Shaker for a vast range of protocols, Versatile Design.

Create your own matrix for vessels of all shapes and sizes with Hi-Lo Platform and Bungee Cords, Instantly adjusts to weight load changes and unbalanced loads with no-stop electronic motor feedback allowing for truly reproducible results, Durable ABS construction suitable for use in incubators (excluding CO₂) and cold rooms within the stated temperature range.

High Featured Operation, Soft stLIST and shut down feature reduces spilling from full vessels, Designed to handle heavy loads up to 10 lbs (4.5 kg), Overload protection shut-off prevents overloading.

Specifications: Speed Range: 20 - 300 rpm, 1 rpm increments, Orbit Diameter: 19.0 mm (0.8"), Run Time Range: 0 to 74 hours and 59 minutes, 1 second increments or continuous, Maximum Load: 4.5 kg (10 lbs.), Ambient conditions: 2° to 40°C (36° to 104°F); 20 to 80% RH, non-condensing, Platform interior dimensions: 11 x 11 in (27.9 x 27.9 cm).

The unit includes: Digital Orbital Shaker, Skid-free Rubber Platform Mat, 8 Bungee Cord Set, Universal hi-lo Platform with Soft Rubber Edge Bumpers, 1 Low Voltage, Double Insulated Power Adapter (110/240VAC, 50/60 Hz) with 4 Interchangeable Plug Types. Certifications: CE, Intertek (US, CA), ROHS3 and WEEE.

| Colore | PZ | Codice Steda |
|--------------|----|--------------|
| Viola-grigio | 1 | LN-72045606 |