

Raccordo-Rubinetto, 2-3 vie, in PP/PE/PVDF

Raccordi-Rubinetto con 2-3 vie in PP/PE e PVDF.

Temperatura PP/PE da +5°C a +40°C, PVDF da +0°C a +40°C.

Modello	Materiale	Per tubi Ø mm	Foro Ø mm	PZ	Codice Steda
2 vie dritte	PP/PE	5-7	4	1	BU-86050060
2 vie dritte	PP/PE	7-9	6	1	BU-86050080
2 vie dritte	PP/PE	9-11	8	1	BU-86050100
2 vie dritte	PP/PE	11-13	8	1	BU-86050120
2 vie dritte	PVDF	5-7	4	1	BU-86070060
2 vie dritte	PVDF	7-9	6	1	BU-86070080
2 vie dritte	PVDF	9-11	8	1	BU-86070100
2 vie dritte	PVDF	11-13	8	1	BU-86070120
3 vie dritte	PP/PE	5-7	4	1	BU-86060060
3 vie dritte	PP/PE	7-9	6	1	BU-86060080
3 vie dritte	PP/PE	9-11	8	1	BU-86060100
3 vie dritte	PP/PE	11-13	8	1	BU-86060120
3 vie dritte	PVDF	5-7	4	1	BU-86080060
3 vie dritte	PVDF	7-9	6	1	BU-86080080
3 vie dritte	PVDF	9-11	8	1	BU-86080100
3 vie dritte	PVDF	11-13	8	1	BU-86080120